


### Series 100A Specifications

Contact Rating	5A with resistive load @ 125VAC or 28VDC
Electrical Life	50,000 make-and-break cycles at full load
Contact Resistance	10mΩ max. initial @ 2-4VDC, 100mA for both silver & gold plated contacts
Insulation Resistance	1000 MΩ min
Dielectric Strength	1500RMS @ sea level
Operating Temp	-30°C to 85°C



#### Model No

#### Action

#### W x L x H (mm)


#### Function

WSP-1  
WSP-2  
WSP-3  
WSP-4  
WSP-5

SP DT

7 x 13 x 17

On None On  
On None (On)  
On Off On  
(On) Off (On)  
On Off (On)



WDP-1  
WDP-2  
WDP-3  
WDP-4  
WDP-5

DP DT

12 x 13 x 17

On None On  
On None (On)  
On Off On  
(On) Off (On)  
On Off (On)



W3P-1  
W3P-2  
W3P-3  
W3P-4  
W3P-5

3P DT

17 x 13 x 19

On None On  
On None (On)  
On Off On  
(On) Off (On)  
On Off (On)

#### Actuator

T1 Standard

T2 Short

#### Bushing

B1 Standard

B4 Short Non Threaded  
(PC Mounting)

#### Termination

M1 Solder Lug

M2 PC Mounting

M6 Right Angle

M7 Vertical

#### Contact Material

Q Silver

G Gold

R Gold (0.4VA max 20V)

**NB** Termination: Straight PC Mounting with Support Bracket available, please request further information

### How To Order

