

Series 200 Specifications

Contact Rating	3A with resistive load @ 125VAC or 28VDC
Electrical Life	30,000 make-and-break cycles at full load
Contact Resistance	10mΩ max. initial @ 2-4VDC, 100mA for both silver & gold plated contacts
Insulation Resistance	1000 MΩ min
Dielectric Strength	1500RMS @ sea level
Operating Temp	-30°C to 85°C



Model No

Action

W x L x H (mm)

Function

MSP-1
MSP-2
MSP-3
MSP-4
MSP-5

SP DT

6 x 9 x 9

On None On
On None (On)
On Off On
(On) Off (On)
On Off (On)



MDP-1
MDP-2
MDP-3
MDP-4
MDP-5

DP DT

10 x 9 x 9

On None On
On None (On)
On Off On
(On) Off (On)
On Off (On)

Actuator

T1 Standard

T2 Short

Bushing

B1 Standard

B2 Standard Non Threaded (PC Mounting)

B3 Short

B4 Short Non Threaded (PC Mounting)

Termination

M1 Solder Lug

M2 PC Mounting

M6 Right Angle

M7 Vertical

Contact Material

Q Silver

G Gold

R Gold (0.4VA max 20V)

NB Termination: Straight PC Mounting with Support Bracket available, please request further information

How To Order

