

Contact Rating	0.4Volt-Amps(VA)max, @ 20V max (AC or DC)
Electrical Life	30,000 make-and-break cycles at full load
Contact Resistance	20mΩ max. initial @ 2-4VDC, 100mA for both silver & gold plated contacts
Insulation Resistance	1000 MΩ min
Dielectric Strength	1500RMS @ sea level
Operating Temp	-30°C to 85°C



Model No	Action	W x L x H (mm)	Function
WMSP-1	SP DT	5 x 8 x 14	On None On
WMSP-2			On None (On)
WMSP-3			On Off On
WMSP-4			(On) Off (On)
WMSP-5			On Off (On)
WMDP-1	DP DT	9 x 8 x 14	On None On
WMDP-2			On None (On)
WMDP-3			On Off On
WMDP-4			(On) Off (On)
WMDP-5			On Off (On)

### Actuator

T1 Standard

T2 Short

### Bushing

B4 Short Non Threaded (PC Mounting)

### Termination

M1 Solder Lug

M2 PC Mounting

M6 Right Angle

M7 Vertical

### Contact Material

Q Silver

G Gold

R Gold (0.4VA max 20V)

**NB** Termination: Straight PC Mounting with Support Bracket available, please request further information

### How To Order

