





Contact Rating	5A with resistive load @ 125VAC or 28VDC
Electrical Life	50,000 make-and-break cycles at full load
Contact Resistance	20mΩ max. initial @ 2-4VDC, 100mA for both silver & gold plated contacts
Insulation Resistance	1000 MΩ min
Dielectric Strength	1500RMS @ sea level
Operating Temp	-30°C to 85°C

	Model No	Action	W x L x H (mm)	Function
	SP-1	SP DT	9 x 30 x 14	On None On
	SP-2			On None (On)
	SP-3			On Off On
	SP-4			(On) Off (On)
	SP-5			On Off (On)
	DP-1	DP DT	12 x 30 x 14	On None On
	DP-2			On None (On)
	DP-3			On Off On
	DP-4			(On) Off (On)
	DP-5			On Off (On)
	3P-1	3P DT	17 x 30 x 14	On None On
	3P-2			On None (On)
	3P-3			On Off On
	3P-4			(On) Off (On)
	3P-5			On Off (On)
	4P-1	4P DT	22 x 13 x 14	On None On
	4P-2			On None (On)
	4P-3			On Off On
	4P-4			(On) Off (On)
	4P-5			On Off (On)

Actuator

- R1 Standard Rocker
- R2 Standard Paddle
- R3 Large Rocker
- R4 Large Paddle
- R6 Snap In Rocker
- R7 Snap In Paddle

Termination

- M1 Solder Lug
- M2 PC Mounting
- M6 Right Angle
- M7 Vertical

Contact Material

- Q Silver
- G Gold
- R Gold (0.4VA max 20V)

NB Termination: Straight PC Mounting with Support Bracket available, please request further information

How To Order

