



## Series 300A Sealed Miniature Rocker & Paddle Switches

Contact Rating	0.4Volt-Amps(VA) max @20V (AC of DC)
Electrical Life	30,000 make-and-break cycles at full load
Contact Resistance	10mΩ max. initial @ 2-4VDC, 100mA for both silver & gold plated contacts
Insulation Resistance	1000 MΩ min
Dielectric Strength	1500 V RMS @ sea level
Operating Temp	-30°C to 85°C

	Model No	Action	W x L x H (mm)	Function
	WSP-1	SP DT	10 x 30 x 14	On None On
	WSP-2			On None (On)
	WSP-3			On Off On
	WSP-4			(On) Off (On)
	WSP-5			On Off (On)
	WDP-1	DP DT	12 x 30 x 14	On None On
	WDP-2			On None (On)
	WDP-3			On Off On
	WDP-4			(On) Off (On)
	WDP-5			On Off (On)
	W3P-1	3P DT	17 x 30 x 14	On None On
	W3P-2			On None (On)
	W3P-3			On Off On
	W3P-4			(On) Off (On)
	W3P-5			On Off (On)

### Actuator

- R1 Standard Rocker
- R2 Standard Paddle
- R3 Large Rocker
- R4 Large Paddle

### Termination

- M1 Solder Lug
- M2 PC Mounting
- M6 Right Angle
- M7 Vertical

### Contact Material

- Q Silver
- G Gold
- R Gold (0.4VA max 20V)

**NB** Termination: Straight PC Mounting with Support Bracket available, please request further information

### How To Order

